

**PRODUCT
DATA SHEET**

DESIGN 250
Vinyl Collection 2012

January 2012

Type of flooring

EN 653

Vinyl Floorcovering

Class of use

EN 685



23



32



41

Class

Description



EN 428

2,50 mm



EN 429

0,35 mm



EN 660-2

Abrasion group

T



EN 430

1,860 kg/m²



EN 426

EN 426

25 m

4+3+2m



EN 425

Castor chair

Fully adhered

OK



EN ISO 717/2

Impact sound absorption

17 dB



EN 433

Static indentation

≤ 0,20 mm

Optional Characteristics



ISO 105/B02

Light fastness

≥ 6



EN 1815

Static electrical propensity

≤ 2 kV



Fire Classification

EN 13501-1

Report N° :

Bfl-s1

RA10-0251



EN 434

Dimensional stability

≤ 0,40 %



Recyclable

OK



EN 423

Chemical resistance

OK



Slip resistance

EN 13893

DIN 51130

≥ 0,30 μ

R10



EN 12524

Thermal resistance for underfloor heating

0,04 m²/kW



EN 14041 : 2004

**Manufactured in EEC by
TARKETT**

DESIGN 250	TARKETT BALANCED CHOICE	58 % Natural	100 % Recyclable	<100 µg/m³ Better Indoor Air Quality <small>*TVOC AT 28 DAYS</small>
-------------------	--------------------------------	------------------------	----------------------------	---